

CATEGORY	INDOOR							REMOTE	OUTDOOR			
FEATURE	AP-103H	AP-103	AP-104/105	AP-204/205	AP-114/115	AP-134/135	AP-224/225	RAP-3WN/RAP-3WNP	RAP-108/109	RAP-155/155P	AP-175P/AP-175AC	AP-274/AP-275
												
NETWORK INTERFACES	1x GE + 2x FE + 1x passthrough RJ-45	1x GE	1x GE	1x GE	1x GE	2x GE	2x GE	3x FE	1x GE + 1x FE	5x GE	1x GE	2x GE
JUMBO FRAME SUPPORT ON UPLINK	No	No	No	✓	No	No	✓	No	No	No	No	✓
USB HOST INTERFACE	No	No	No	No	✓	No	✓	✓	✓	✓	No	No
CONSOLE PORT	Header	Header	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	Header	RJ-45	Header	USB Type A	Micro USB
POE PD POWER	3af	3af	3af	3af	3af/3at	3af	3af/3at	No	3af/at	No	3at	3at
POE PSE	No	No	No	No	No	No	No	No/802.3af	No	No/802.3at (1x) or 802.3af (2x)	✓ (AP-175AC)	No
DC POWER SUPPORT	12V	12V	12V	12V	12V	12V	12V	12V / 48V	12V	12V / 54V	N/A	N/A
SHIPS WITH AC-TO-DC ADAPTER	No	No	No	No	No	No	No	✓ (cord not included for RAP-3WNP)	No	✓ (cord not included for RAP-155P)	No	No
TEMPERATURE RANGE	0° C to +40° C	0° C to +40° C	0° C to +50° C	0° C to +40° C	0° C to +50° C	0° C to +50° C	0° C to +50° C	0° C to +40° C	0° C to +40° C	0° C to +40° C	-40° C to +50° C	-40° C to +65° C
ENCLOSURE TYPE	Plastic	Plastic	Plastic/metal	Plastic/metal	Plastic/metal	Plastic/metal	Plastic/metal	Plastic	Plastic	Plastic	Plastic/metal	Plastic/metal
ENCLOSURE VOLUME (MM)	140 x 86 x 30	150 x 150 x 41.5	132 x 135 x 45	150 x 150 x 41.5	180 x 180 x 45	170 x 170 x 45	203 x 203 x 54	129 x 109 x 64	181 x 160 x 72	185 x 245 x 65	225 x 225 x 105	230 x 230 x 190 (AP-274) 230 x 240 x 270 (AP-275)
WEIGHT (UNIT ONLY, WITH DESK MOUNT)	260 g	300 g	300 g	380 g	650 g	760 g	750 g	180 g	460 g	700 g	3,500 g	2,700 g (AP-274) 2,400 g (AP-275)
PLENUM RATED	No	No	✓	✓	✓	✓	✓	No	No	No	No	No

CATEGORY	INDOOR							REMOTE	OUTDOOR			
FEATURE	AP-103H	AP-103	AP-104/105	AP-204/205	AP-114/115	AP-134/135	AP-224/225	RAP-3WN/RAP-3WNP	RAP-108/109	RAP-155/155P	AP-175P/AP-175AC	AP-274/AP-275
												
TAA/FIPS VERSION AVAILABLE	No	No	✓	No	✓	✓	✓	✓	✓	✓	No	No
LIFETIME WARRANTY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	No	✓
MINIMUM SOFTWARE VERSION	ArubaOS 6.4.1.0	ArubaOS 6.4.0.0 InstantOS 4.1.0.0	ArubaOS 3.4.1.0 (AP-105) ArubaOS 6.1.3.0 (AP-104) InstantOS 2.0.0.3	ArubaOS 6.4.1.0 InstantOS 4.2.0.0	ArubaOS 6.3.1.0 InstantOS 4.0.0.0	ArubaOS 6.1.1.0 InstantOS 2.0.0.3	ArubaOS 6.3.0.0 InstantOS 4.0.0.0	ArubaOS 6.1.4.0 InstantOS 3.0.0.0	ArubaOS 6.2.0.0 InstantOS 3.2.0.0	ArubaOS 6.3.0.0 InstantOS 3.3.0.1	ArubaOS 5.0.2.1 InstantOS 2.0.0.3	ArubaOS 6.4.0.0 InstantOS 4.1.0.0
SPECTRUM ANALYSIS SUPPORT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
MAXIMUM POWER CONSUMPTION (EXCLUDING USB, POE PSE)	8.3W (DC) 9.4W (PoE)	8W (DC) 9.5W (PoE)	10W (DC) 12.5W (PoE)	11.7W (DC) 12.5W (PoE)	12W (DC) 13W (PoE)	12W (DC) 13.5W (PoE)	15W (DC) 12.5W/15.5W (PoE)	4.0W/5.5W	12.5W	15.5W	18W	23W
MAX IPSEC ENCRYPTED WIRED THROUGHPUT (RAP MODE)	10	10	15	20	20	40	100	20	20	100	15	20



1344 CROSSMAN AVE | SUNNYVALE, CA 94089
 1.866.55.ARUBA | T: 1.408.227.4500 | FAX: 1.408.227.4550 | INFO@ARUBANETWORKS.COM